



E32-LD11 2M

Fiber optic sensor head, diffuse, M6 cylindrical axial, integrated lens, R25 fiber, 2 m cable

Sensing method	Diffuse reflective
Shape	Threaded
Size	M6
Application	Object detection
Temperature range	-40-70 °C
Sensing distance	1290 mm
Cable length	2 m
Bending radius	25 mm
Free cut	✓
Material core	Plastic
Degree of protection (IP)	IP50
Sensing surface orientation	Top-view
Material sheath	Polyethylene



E3NX-CA

Yüksek performanslı renk işareti sensörü



E3NX-FA

Yüksek performanslı dijital fiber yükseltici



E3NX-MA

Akıllı Fiber Amplifikatör Üniteleri



E3NX-CA

Yüksek performanslı renk işareti sensörü



E3X-NA

Potansiyometre ayarlı dijital fiber yükseltici



E3X-ZV ve E3X-MZV

Akıllı Fiber Amplifikatör

CAD Kütüphanesi



E32-LT/LD Build-in Lens Veri Sayfası

EN PDF 1,22 MB



E32-LT/LD Hex-shaped Fiber Unit Broşür

EN PDF 6,35 MB



EAC Mark removal Üretimden Kaldırılma Bildirimi

EN PDF 221 KB



Fiber Sensor Selection Seçim Kılavuzu

EN PDF 16,2 MB

WEB SİTESİ KULLANIM KOŞULLARI

Bu PDF belgesi, 14 May, 2024 tarihinde OMRON Endüstriyel Otomasyon Avrupa web sitesinden oluşturulmuştur. [yasal duyurular](#) için buraya tıklayın.